



Product Description

Self-Support Cable is a solid insulated, single jacket air core design with a built-in support member intended specifically for aerial applications. The undulated, shielded core is laid parallel to a flooded steel support member and jacketed in an integral extrusion to form a “figure 8” configuration. The supporting member is an integral part of the cable sheath yet readily available for gripping, pulling and tensioning. Installation is fast and easy using standard methods and hardware.

Applications

- Aerial

Specifications	
Conductor	Solid annealed copper
Insulation	Solid polyolefin in distinctive colors to facilitate pair identification
≤ 25-Pair Core	Pairs are combined into a cylindrical core
> 50-Pair Core	Multiples of 25-pair groups are assembled to form the final cable core; each group is identified by color coded non-hygroscopic binders
Core Wrap	Non-hygroscopic dielectric material
Shield	Corrugated, 8 mil coated aluminum tape applied longitudinally over the core wrap
Support Member	0.25 inch, 7-strand Extra High-Strength (EHS) galvanized steel member, fully flooded, serves as the support member and is an integral part of the sheath
Jacket	Black polyethylene
Jacket Marking	Manufacturer's identification, pair count, AWG, product identification, sequential footage and a telephone handset printed at 2 foot intervals
Standards Compliance	Telcordia GR-421-CORE Issue 2 RoHS-compliant

Features

- Tightly controlled individual conductor dimensions
- Specially designed pair twist lays
- Undulated core assembly
- Core wrap
- Fully flooded steel support member
- Polyethylene jacket

Benefits

- Limits resistance unbalance of paired conductors
- Minimizes crosstalk and meets the capacitance unbalance requirements
- Eliminates strain on the conductors and provides sufficient slack during installation
- Protects the core and helps provide core-to-shield dielectric strength
- Provides corrosion protection
- Provides tough, flexible, protective covering that withstands exposure to sunlight, atmospheric temperatures and stresses expected in standard installations

Electrical Specifications

Number of Pairs	Average Mutual Capacitance @ 1000 Hz nF/mile (nF/km)	Capacitance Unbalance Pair to Pair @ 1 kHz		Capacitance Unbalance Pair to Ground @ 1 kHz	
		Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum RMS pF @ 1 kft (pF @ 1 km)	Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum Average pF @ 1 kft (pF @ 1 km)
Over 12	83 + 4, - 5 (52 + 2, - 3)	80 (145)	25 (45)	800 (2,625)	175 (574)

Conductor Size AWG (mm)	Minimum Insulation Resistance @ 68°F (20°C) gigohm-mile (gigohm-km)	Maximum Average Attenuation 772 kHz @ 68°F (20°C) dB/kft (dB/km)	Maximum Conductor Resistance @ 68°F (20°C) Ohms/sheath mile (km)	DC Resistance Unbalance Maximum %		Dielectric Strength DC Potential – Volts	
				Average	Individual Pair	Conductor to Conductor	Conductor to Shield
22 (0.64)	1.0 (1.6)	4.7 (15.4)	91 (56.5)	1.5	5.0	4,000	10,000
24 (0.51)	1.0 (1.6)	5.9 (19.4)	144 (89.5)	1.5	5.0	3,000	10,000

Minimum Near End Crosstalk (NEXT) @ 772 kHz		Minimum Far End Crosstalk (FEXT) @ 772 kHz	
PSWUNEXT Mean (dB)	47	Conductor Size (AWG)	22 24
PSWUNEXT Worst Pair (dB)	42	PSELFEXT Mean (dB/kft)	49 49
		PSELFEXT Worst Pair (dB/kft)	43 43

Part Numbers and Physical Characteristics

Part Number	Product Code	Pair Count	AWG (mm)	Nominal Diameter		Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Approx. Shipping Weight lbs (kg)	Steel Reel Size F x T x D in
				Cable only in (mm)	W/Messenger in (mm)				
120-062-43	BHAS	25	22 (0.64)	0.58 (15)	1.05 (27)	310 (461)	10,000 (3,048)	3,895 (1,766)	83 x 40 x 42
120-065-43	BHAS	50	22 (0.64)	0.74 (19)	1.20 (31)	445 (662)	7,500 (2,286)	4,135 (1,875)	83 x 40 x 42
120-069-43	BHAS	100	22 (0.64)	1.00 (25)	1.47 (37)	705 (1,049)	6,000 (1,829)	5,025 (2,279)	83 x 40 x 42
120-097-43	BKMS	25	24 (0.51)	0.49 (12)	0.96 (24)	260 (387)	13,300 (4,054)	4,255 (1,930)	83 x 40 x 42
120-100-43	BKMS	50	24 (0.51)	0.62 (16)	1.09 (28)	345 (513)	13,300 (4,054)	5,385 (2,442)	83 x 40 x 42
120-104-43	BKMS	100	24 (0.51)	0.80 (20)	1.27 (32)	515 (766)	8,000 (2,438)	4,915 (2,229)	83 x 40 x 42
120-108-43	BKMS	200	24 (0.51)	1.09 (28)	1.56 (40)	840 (1,250)	5,000 (1,524)	4,995 (2,265)	83 x 40 x 42

REINFORCED SELF-SUPPORT

BHAP, BKMP and BKTP

Product Description

Reinforced Self-Support Cable is a solid insulated, double jacket, armored, self-supporting air core design intended for aerial installations where hazards from squirrel attack, tree limb abrasion or lightning exist. The undulated, shielded, jacketed core is covered with a flooded steel armor, laid parallel to a flooded steel support member and jacketed in an integral extrusion to form a “figure 8” configuration. The steel strand member is readily available for gripping, pulling and tensioning using standard methods and hardware.

Applications

- Aerial installations in harsh environments

Features

- Tightly controlled individual conductor dimensions
- Specially designed pair twist lays
- Undulated core assembly
- Core wrap
- Inner polyethylene jacket
- Flooded steel support member
- Polyethylene jacket

Benefits

- Limits resistance unbalance of paired conductors
- Minimizes crosstalk and meets the capacitance unbalance requirements
- Eliminates strain on the conductors and provides sufficient slack during installation
- Protects the core and helps provide core-to-shield dielectric strength
- Provides additional protection against mechanic damage and prevents the ingress of moisture
- Provides corrosion protection
- Provides tough, flexible, protective covering that withstands exposure to sunlight, atmospheric temperatures and stresses



Specifications

Conductor	Solid annealed copper
Insulation	Solid polyolefin in distinctive colors to facilitate pair identification
≤ 25-Pair Core	Pairs are combined into a cylindrical core
> 50-Pair Core	Multiples of 25-pair groups are assembled to form the final cable core; each group is identified by color coded non-hygroscopic binders
Core Wrap	Non-hygroscopic dielectric material
Shield	Corrugated, 8 mil aluminum tape is applied longitudinally over the core wrap
Inner Jacket	Polyethylene helps protect the core and shield against mechanical damage and ingress of moisture
Armor	Corrugated bare 6 mil steel tape is applied longitudinally over the inner jacket and the inner and outer surfaces of the steel are flooded
Support Member	0.25 inch, 7-strand Extra High-Strength (EHS) galvanized steel member, fully flooded, serves as the support member and is an integral part of the sheath
Outer Jacket	Black polyethylene
Jacket Marking	Manufacturer's identification, pair count, AWG, product identification, sequential footage and a telephone handset printed at 2 foot intervals
Standards Compliance	Telcordia GR-421-CORE Issue 2 RoHS-compliant

Electrical Specifications

Number of Pairs	Average Mutual Capacitance @ 1000 Hz nF/mile (nF/km)	Capacitance Unbalance Pair to Pair @ 1 kHz		Capacitance Unbalance Pair to Ground @ 1 kHz	
		Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum RMS pF @ 1 kft (pF @ 1 km)	Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum Average pF @ 1 kft (pF @ 1 km)
Over 12	83 + 4, - 5 (52 ± 2, - 3)	80 (145)	25 (45)	800 (2,625)	175 (574)

Conductor Size AWG (mm)	Minimum Insulation Resistance @ 68°F (20°C) gigohm-mile (gigohm-km)	Maximum Average Attenuation 772 kHz @ 68°F (20°C) dB/kft (dB/km)	Maximum Conductor Resistance @ 68°F (20°C) Ohms/sheath mile (km)	DC Resistance Unbalance Maximum %		Dielectric Strength DC Potential – Volts	
				Average	Individual Pair	Conductor to Conductor	Conductor to Shield
22 (0.64)	1.0 (1.6)	4.7 (15.4)	91 (56.5)	1.5	5.0	4,000	10,000
24 (0.51)	1.0 (1.6)	5.9 (19.4)	144 (89.5)	1.5	5.0	3,000	10,000
26 (0.40)	1.0 (1.6)	7.4 (24.3)	232 (144.2)	1.5	5.0	2,400	10,000

Minimum Near End Crosstalk (NEXT) @ 772 kHz		Minimum Far End Crosstalk (FEXT) @ 772 kHz	
PSWUNEXT Mean (dB)	47	Conductor Size (AWG)	22 24 26
PSWUNEXT Worst Pair (dB)	42	PSELFEXT Mean (dB/kft)	49 49 47
		PSELFEXT Worst Pair (dB/kft)	43 43 43

Part Numbers and Physical Characteristics

Part Number	Product Code	Pair Count	AWG (mm)	Nominal Diameter		Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Approx. Shipping Weight lbs (kg)	Steel Reel Size F x T x D in
				Cable only in (mm)	W/Messenger in (mm)				
120-062-20	BHAP	25	22 (0.64)	0.87 (22)	1.33 (34)	455 (675)	10,000 (3,048)	4,200 (1,905)	83 x 40 x 42
120-065-20	BHAP	50	22 (0.64)	1.05 (27)	1.51 (38)	625 (930)	7,500 (2,286)	4,465 (2,025)	83 x 40 x 42
120-069-20	BHAP	100	22 (0.64)	1.30 (33)	1.76 (45)	940 (1,400)	5,000 (1,524)	4,475 (2,029)	83 x 40 x 42
120-097-20	BKMP	25	24 (0.51)	0.83 (21)	1.29 (33)	400 (595)	10,000 (3,048)	4,345 (1,971)	83 x 40 x 42
120-100-20	BKMP	50	24 (0.51)	0.94 (24)	1.40 (36)	510 (760)	10,000 (3,048)	5,445 (2,469)	83 x 40 x 42
120-104-20	BKMP	100	24 (0.51)	1.13 (29)	1.59 (40)	715 (1,065)	5,000 (1,524)	4,145 (1,880)	83 x 40 x 42
120-108-20	BKMP	200	24 (0.51)	1.42 (36)	1.88 (48)	1,120 (1,665)	4,000 (1,220)	4,995 (2,265)	83 x 40 x 42
120-145-20	BKTP	300	26 (0.40)	1.35 (34)	1.81 (46)	1,045 (1,555)	3,300 (1,010)	4,110 (1,864)	83 x 40 x 42