

Product Description

Loose tube cables are the product of choice as the backbone in Outside Plant (OSP) environments. The rugged loose tube design offers reliable transmission performance over a broad temperature range. Optical fibers are placed inside filled buffer tubes containing PFM™ gel. The core is constructed by stranding the buffer tubes around a central member using a reverse oscillating lay (ROL). The core is wrapped with flexible strength members covered with a water-blocking tape then encased with a black inner jacket. Water-blocking yarns and a corrugated steel armor are applied and a black outer jacket completes the cable construction. Rip cords are included under the inner jacket and armor for ease of entry.

Applications


- Direct bury, underground duct and lashed aerial
- Trunk, distribution and feeder cables
- Local loop, metro, long-haul and broadband network

Features

- Available with up to 288-fiber
- Multiple fiber types including hybrids
- Dry (SAP) core standard
- Standard tube size for all fiber counts
- Corrugated steel armor
- PFM gel

Benefits

- High fiber density
- Multiple network applications
- Reduces cable prep and installation time
- Reduces the number of tools required
- Improves compressive strength and rodent protection
- Non-sticky gel speeds fiber access and clean-up



Specifications

Fiber Count	Available in 2-fiber up to 288-fiber
Standards Compliance	Telcordia GR-20-CORE RDUP PE-90 Designation MLT ICEA S-87-640-2006 RoHS-compliant

Environmental Specifications

Operation/Storage	-40°C to +70°C
Installation	-30°C to +70°C

Part Numbers and Physical Characteristics

Part Number ¹	Fiber Count	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Maximum Tensile Loading		Minimum Bend Radius	
				Install lbs (N)	Long Term lbs (N)	Install in (mm)	Long Term in (mm)
11A006xx01	6	0.56 (14.1)	119 (178)	600 (2,700)	200 (890)	11.2 (282)	5.6 (141)
11A012xx01	12	0.56 (14.1)	119 (178)	600 (2,700)	200 (890)	11.2 (282)	5.6 (141)
11A024xx01	24	0.56 (14.1)	119 (178)	600 (2,700)	200 (890)	11.2 (282)	5.6 (141)
11A036xx01	36	0.56 (14.1)	119 (178)	600 (2,700)	200 (890)	11.2 (282)	5.6 (141)
11A048xx01	48	0.56 (14.1)	119 (178)	600 (2,700)	200 (890)	11.2 (282)	5.6 (141)
11A072xx01	72	0.58 (14.9)	138 (206)	600 (2,700)	200 (890)	11.6 (298)	5.8 (149)
11A096xx01	96	0.65 (16.6)	166 (248)	600 (2,700)	200 (890)	13.0 (322)	6.5 (166)
11A144xx01	144	0.78 (19.9)	230 (343)	600 (2,700)	200 (890)	15.6 (398)	7.8 (199)
11A216xx01	216	0.78 (19.9)	226 (336)	600 (2,700)	200 (890)	15.6 (398)	7.8 (199)
11A288xx01	288	0.90 (22.9)	283 (422)	600 (2,700)	200 (890)	18.0 (458)	9.0 (229)

Part Number Key

1	A	-	-	-	x	x	0	-
1	2	3	4	5	6	7	8	9
Product family	Fiber count (002-288)			Fiber type	Internal designator	Water block/ marking (1-8)		

Contact Customer Service for availability of non-standard offerings.
See "Optical Fiber Cable" options in the "Technical Information" section for flooding and jacket marking options.

Single Mode Optical Fiber Types

	Conventional	Reduced Water Peak	Zero Water Peak	TeraFlex® Bend Resistant			
				G.657.A1	G.657.A2	G.657.B3	NZDS
¹ For ≤ 36 fibers replace "xx" with:	9T	3T	2T	KT	JT	LT	8T
¹ For > 36 fibers replace "xx" with:	91	31	21	K1	J1	L1	81

Multimode Optical Fiber Types

	TeraGain Laser Optimized 50/125			
	TeraGain® 62.5/125	10G/150	10G/300	10G/550
¹ Replace "xx" with:	6G	AG	BG	FG