

Product Description

Distribution Frame Wires are designed for cross-connection of equipment in telephone switch and equipment rooms requiring point-to-point hook ups.



Applications

- Normal use

Features

- Solid tinned copper conductors in 22 AWG or 24 AWG are insulated with semi-rigid polyvinyl chloride (PVC)
- Each insulated conductor is identified by a solid insulation color

Benefits

- Facilitates wire wrapping and tight connections
- Easy identification

Specifications

Conductor	Tinned copper
Insulation	Semi-rigid PVC
Performance Compliance	ASTM B33 - Tinned Copper UL 444 CSA C22.2 No. 214-08 GR 136 CORE (normal use) RoHS-compliant
NRTL Programs	UL, c(UL) Listed CM

Part Numbers and Physical Characteristics

Part Number	Number of Conductors	AWG (mm)	Insulation Color	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Package
112-001-11	1	22 (0.6)	Red	0.04 (1.0)	2 (3)	750 m Spool
112-002-11	1	22 (0.6)	White	0.04 (1.0)	2 (3)	750 m Spool
112-003-11	1	22 (0.6)	Green	0.04 (1.0)	2 (3)	750 m Spool
112-004-11	1	22 (0.6)	Black	0.04 (1.0)	2 (3)	750 m Spool
112-303-13	1	22 (0.6)	Green	0.04 (1.0)	2 (3)	1,000 m Spool
112-326-11	1	22 (0.6)	Brown	0.04 (1.0)	2 (3)	3,000' Spool
112-001-12	2	22 (0.6)	Red/Green	0.08 (2.0)	5 (7)	500 m Spool
112-003-12	2	22 (0.6)	Blue/White	0.08 (2.0)	5 (7)	500 m Spool
112-004-12	2	22 (0.6)	Brown/Blue	0.08 (2.0)	5 (7)	500 m Spool
112-005-12	2	22 (0.6)	Black/White	0.08 (2.0)	5 (7)	500 m Spool
112-001-13	2	22 (0.6)	Red/White	0.08 (2.0)	5 (7)	305 m Spool
112-003-13	2	22 (0.6)	Blue/White	0.08 (2.0)	5 (7)	1,000' Spool
112-005-13	2	22 (0.6)	Black/White	0.08 (2.0)	5 (7)	1,000' Spool
112-101-13	2	24 (0.5)	Red/White	0.08 (2.0)	4 (6)	1,000' Spool
112-102-13	2	24 (0.5)	Red/Yellow	0.08 (2.0)	4 (6)	1,000' Spool
112-103-13	2	24 (0.5)	White/Blue	0.08 (2.0)	4 (6)	1,000' Spool
112-104-13	2	24 (0.5)	Violet/Blue	0.08 (2.0)	4 (6)	305 m Spool
112-105-13	2	24 (0.5)	Black/White	0.08 (2.0)	4 (6)	1,000' Spool
112-106-13	2	24 (0.5)	Red/White	0.08 (2.0)	4 (6)	6,000' Spool
112-107-13	2	24 (0.5)	Black/White	0.08 (2.0)	4 (6)	6,000' Spool
112-108-13	2	24 (0.5)	White/Blue	0.08 (2.0)	4 (6)	6,000' Spool
112-109-13	2	24 (0.5)	Yellow/Blue	0.08 (2.0)	4 (6)	1,000' Spool
112-112-13	2	24 (0.5)	Red/White	0.08 (2.0)	4 (6)	3,000' Parallel cone
112-203-13	2	22 (0.6)	Blue/White	0.08 (2.0)	5 (7)	400' Spool
112-304-13	2	22 (0.6)	Brown/Blue	0.08 (2.0)	5 (7)	1,000 m Parallel cone
112-305-13	2	22 (0.6)	Black/White	0.08 (2.0)	5 (7)	1,000 m Parallel cone
112-311-13	2	22 (0.6)	Red/Green	0.08 (2.0)	5 (7)	3,000' Spool
112-313-13	2	22 (0.6)	Blue/White	0.08 (2.0)	5 (7)	3,280' Parallel cone
112-318-13	2	22 (0.6)	White/Orange	0.08 (2.0)	5 (7)	3,000' Spool
112-403-13	2	22 (0.6)	White/Blue	0.08 (2.0)	5 (7)	3,000' Spool
112-406-13	2	22 (0.6)	Yellow/Violet	0.08 (2.0)	5 (7)	3,000' Spool
112-501-13	2	22 (0.6)	Red/White	0.08 (2.0)	5 (7)	2,300' Spool
112-031-12	4	22 (0.6)	Blue/White, Red/Green	0.12 (3.0)	9 (13)	1,640' Parallel cone
112-032-13	4	22 (0.6)	Black/White, Black/White	0.12 (3.0)	9 (13)	1,640' Parallel cone
112-033-13	4	22 (0.6)	Yellow/Blue, Orange/Brown	0.12 (3.0)	9 (13)	1,640' Parallel cone
112-034-13	5	22 (0.6)	Yellow/Blue, Orange/Brown, Green	0.17 (4.3)	13 (20)	500 m Parallel cone
112-035-13	5	22 (0.6)	Black/White, Black/White, Green	0.17 (4.3)	13 (20)	500 m Parallel cone