

PRODUCT LINE CARD

		Product Name	Information
GROUND WIRE		Bare Copper Series 6000	APPLICATIONS: <ul style="list-style-type: none"> Suitable for distribution applications, uninsulated hookups, jumpers and grounds in electrical constructions OPTIONS: <ul style="list-style-type: none"> Solid or stranded
LV INSTRUMENTATION		300 Volts PVC/PVC, 300V Type PLTC/ITC, Pairs and Triads Series E1AC	APPLICATIONS: <ul style="list-style-type: none"> Control systems, audio, intercom, alarm circuit, and energy management OPTIONS: <ul style="list-style-type: none"> Available in 1-pair through 36 pairs, and 1-triad through 24 triads Individually and/or overall shields (aluminum polyester foil)
		600 Volts PVC/Nylon/PVC, 600V Instrumentation, Type TC-ER, Pairs and Triads Series E1BE	
		600 Volts XLPE/PVC, 600V Instrumentation, Type TC-ER, Pairs and Triads Series E1BF	
LV CONTROL		600 Volts PE/PVC/PVC, 600V Control (20/10) Series E2BD	APPLICATIONS: <ul style="list-style-type: none"> Industrial power or station control circuits OPTIONS: <ul style="list-style-type: none"> Available in 2 through 37 conductors Unshielded or shielded (aluminum polyester foil or copper tape shield)
		600 Volts PVC/Nylon/PVC, 600V Control, Type TC-ER Series E2BE	
		600 Volts XLPE/PVC, 600V Control, Type TC-ER Series E2BF	
LV POWER		600 Volts PVC/NYLON/PVC, 600V Power, Type TC-ER Series E3BE	APPLICATIONS: <ul style="list-style-type: none"> Commercial and industrial power circuits OPTIONS: <ul style="list-style-type: none"> Available in 3 or 4 conductors plus a bare ground
		600 Volts XLPE/PVC, 600V Power, Type TC-ER Series E3BF	
		600 Volts XLPE/PVC, 600V Power, Type TC-ER, AL-8000 Series E3BF	
MV POWER		5kV - 35 kV EPR/Cu Tape Shield/PVC MV Power, Type MV-105 Series E8xLE	APPLICATIONS: <ul style="list-style-type: none"> Commercial and industrial power circuits OPTIONS: <ul style="list-style-type: none"> Available in 1 or 3 conductors, bare copper stranded 2 AWG through 500 kcmil 100% or 133% insulation level
		5kV - 15 kV EPR/Cu Tape Shield/PVC MV Power, Type MV-5KV-15KV	

PRODUCT LINE CARD

		Product Name	Listing	Part Number	Conductor Count	AWG (mm)	Jacket Color	Nominal Diameter in (mm)	Package
Fire Alarm	<p>Fire Alarm, Non-Shielded Power Limited</p>	FPLR/CL3R	2F-312-91	2	14 (1.63)	Red	0.21 (5.4)	1,000' Ribbed spool	
		FPLR/CL3R/CMR	2F-112-91		18 (1.02)	Red	0.15 (3.8)		
		FPLP/CL3P	2F-312-93		14 (1.63)	Red	0.23 (5.9)		
		FPLP/CL3P/CMP	2F-112-93		18 (1.02)	Red	0.15 (3.8)		
		FPLR/CL3R	2F-333-91	4	14 (1.63)	Red	0.25 (6.4)		500' Ribbed spool
		FPLR/CL3R/CMR	2F-132-91		18 (1.02)	Red	0.17 (4.4)		1,000' Ribbed spool
		FPLP/CL3P	2F-333-93		14 (1.63)	Red	0.27 (6.9)		500' Ribbed spool
	<p>Fire Alarm, Shielded Power Limited</p>	FPLP/CL3P/CMP	2F-132-93	2	18 (1.02)	Red	0.17 (4.4)	1,000' Ribbed spool	
		FPLR/CL3R	2F-312-92		14 (1.63)	Red	0.22 (5.7)	1,000' Ribbed spool	
		FPLR/CL3R/CMR	2F-112-92		18 (1.02)	Red	0.16 (4.1)		
		FPLP/CL3P	2F-312-94		14 (1.63)	Red	0.24 (6.2)		
		FPLP/CL3P/CMP	2F-112-94	18 (1.02)	Red	0.16 (4.1)			
		FPLR/CL3R	2F-333-92	4	14 (1.63)	Red	0.26 (6.6)		500' Ribbed spool
		FPLR/CL3R/CMR	2F-132-92		18 (1.02)	Red	0.18 (4.7)		1,000' Ribbed spool
FPLP/CL3P	2F-333-94	14 (1.63)	Red		0.28 (7.1)	500' Ribbed spool			
<p>Interlock Armored Fire Alarm Riser, Non-Shielded</p>	FPLR/CL3R	K2F-419-91	2	12 (2.05)	Red	0.50 (12.7)	1,000' Wood reel		
	FPLR/CL3R	K2F-339-91	4	14 (1.63)	Red	0.50 (12.7)			
	FPLR/CL3R/CMR	K2F-229-91	3	16 (1.29)	Red	0.50 (12.7)			
<p>Interlock Armored Fire Alarm Riser, Shielded</p>	FPLR/CL3R	K2F-419-92	2	12 (2.05)	Red	0.50 (12.7)	1,000' Wood reel		
	FPLR/CL3R	K2F-339-92	4	14 (1.63)	Red	0.50 (12.7)			
	FPLR/CL3R/CMR	K2F-229-92	3	16 (1.29)	Red	0.50 (12.7)			
Security Control	<p>Security Control, Non-Shielded Power Limited</p>	CL3R/FPLR	2F-E12-31	2	14 (1.85)	Gray	0.23 (5.9)	1,000' Ribbed spool	
		CL3R/CMR/FPLR	2F-C12-31		18 (1.16)	Gray	0.16 (4.1)		
		CL3P/FPLP	2F-E12-43		14 (1.85)	White	0.25 (6.4)		
		CL3P/CMP/FPLP	2F-C12-43		18 (1.16)	White	0.16 (4.1)		
		CL3R/FPLR	2F-E33-31	4	14 (1.85)	Gray	0.27 (6.9)		500' Ribbed spool
		CL3R/CMR/FPLR	2F-C32-31		18 (1.16)	Gray	0.19 (4.8)		1,000' Ribbed spool
		CL3P/FPLP	2F-E33-43		14 (1.85)	White	0.29 (7.4)		500' Ribbed spool
		CL3P/CMP/FPLP	2F-C32-43		18 (1.16)	White	0.19 (4.8)		1,000' Ribbed spool
	<p>Security Control, Shielded Power Limited</p>	CL3R/FPLR	2F-E12-32	2	14 (1.85)	Gray	0.24 (6.1)	1,000' Ribbed spool	
		CL3R/CMR/FPLR	2F-C12-32		18 (1.16)	Gray	0.17 (4.3)		
		CL3P/FPLP	2F-E12-44		14 (1.85)	White	0.26 (6.6)		
		CL3P/CMP/FPLP	2F-C12-44	4	18 (1.16)	White	0.17 (4.3)		
		CL3R/FPLR	2F-E33-32		14 (1.85)	Gray	0.28 (7.2)		500' Ribbed spool
		CL3R/CMR/FPLR	2F-C32-32		18 (1.16)	Gray	0.20 (5.0)		1,000' Ribbed spool
Coaxial	<p>Coax RG-6, Quad Shield CM/CATV, CMR/CATVR and CMP/CL2P</p>	CM/CATV	78-147-9P	-	18 (1.02)	White	0.30 (7.5)	1,000' POP box	
			79-147-9P		18 (1.02)	Black			
		CMR/CATVR	78-148-91		18 (1.02)	White		1,000' Reel	
			79-148-91		18 (1.02)	Black			
		CMP/CL2P	78-14C-91	18 (1.02)	White	0.26 (6.7)	1,000' Reel		
	<p>Coax RG-6, Quad Shield Aluminum Interlock Armored</p>	CMR	KC-919-45 ³	-	18 (1.02)	White	0.53 (13.5)	1,000' Reel	
			KC-919-E5 ³		18 (1.02)	Black			
	<p>Coax RG-6, 80% Shield</p>	CMP/CL2P	78-16C-91	-	18 (1.02)	White	0.23 (5.9)	1,000' Reel	
<p>Coax RG-6, Tri-Shield 70%</p>		CM	78-11A-9R	-	18 (1.02)	White	0.28 (7.1)	1,000' Reel-in-a-Box	
			79-11A-9R		18 (1.02)	Black			
<p>Coax RG-6, 60% Shield</p>		CM	78-107-9P	-	18 (1.02)	White	0.28 (7.1)	1,000' POP box	
			79-107-9P		18 (1.02)	Black			
<p>Coax RG-59, 95% Shield</p>		CMP/CL2P	78-55C-91	-	20 (0.81)	White	0.19 (5.1)	1,000' Reel	